



01 / PRODUCT OVERVIEW

122 mm blank (salute) round

Blank



FIG 01 PRODUCT CONFIGURATION

122 mm	4.41 kg	max 447 mm	min 100 m
CALIBRE	ROUND MASS	ROUND LENGTH	MUZZLE SAFETY

01.1 / OVERVIEW

A 122 mm blank round made up of a cartridge case M78 loaded with a propellant charge and igniter and fired by a gun primer KT M71, used to simulate live firing during manoeuvres, exercises and tactical operations and for gun salutes.

TYPE	CALIBRE	STANDARD
Blank	122 mm	Eastern

PROCUREMENT AND COMPLIANCE

Supply is exclusively for government and institutional end-users. Availability is subject to destination screening, a state-issued export licence and a verified End-User Certificate.



02 / TECHNICAL SPECIFICATION

TECHNICAL DATA

122 mm blank (salute) round / AMMUNITION

IDENTITY AND CONSTRUCTION

Calibre	122 mm
Cartridge case mass	3.66 kg
Cartridge case	122 mm M78

BALLISTIC PERFORMANCE

Operating temperature	-30 to +50 °C
-----------------------	---------------

DIMENSIONS, MASS AND SUPPLY

Round length	max 447 mm
Round mass	4.41 kg
Propellant charge mass	350 g
Igniter (black powder No 7) mass	50 g

ADDITIONAL TECHNICAL DATA

Muzzle safety	min 100 m
Noise level	min 100 dB
Powder	NC-01
Gun primer	KT M71
Guns	122 mm howitzers D-30, D-30J and SP 2S1