



01 / PRODUCT OVERVIEW

20 mm x 110 API-T

20x110 mm API-T round



FIG 01 PRODUCT CONFIGURATION

840±10

MUZZLE VELOCITY (M/S)

273±6

ROUND MASS (G)

20

CALIBRE (MM)

304.1MAXIMUM PRESSURE OF POWDER GASES
(MPA)

01.1 / OVERVIEW

Round consisting of a brass cartridge case with a percussion gun primer, propellant charge and an armour-piercing incendiary tracer projectile filled with incendiary and tracer compositions, with a tracer burning at least 2 seconds.

TYPE

AP

CALIBRE

20x110 mm

STANDARD

NATO

PROCUREMENT AND COMPLIANCE

Supply is exclusively for government and institutional end-users. Availability is subject to destination screening, a state-issued export licence and a verified End-User Certificate.



TECHNICAL DATA

20 mm x 110 API-T / AMMUNITION

IDENTITY AND CONSTRUCTION

Calibre (mm)	20
Projectile mass (g)	142±2.5

BALLISTIC PERFORMANCE

Muzzle velocity (m/s)	840±10
Maximum pressure of powder gases (MPa)	304.1

DIMENSIONS, MASS AND SUPPLY

Round mass (g)	273±6
----------------	-------

ADDITIONAL TECHNICAL DATA

Tracer burning time (s)	min 2
-------------------------	-------