



01 / PRODUCT OVERVIEW

30 mm x 165, PELE

30x165 mm PELE round



FIG 01 PRODUCT CONFIGURATION

970±15 m/s

MUZZLE VELOCITY

400±6 g

PROJECTILE MASS

30 mm

CALIBRE

853 g

ROUND MASS

01.1 / OVERVIEW

A 30 mm x 165 round in an early development phase, consisting of a steel cartridge case with a percussion gun primer, propellant charge and a fragmenting armour-piercing projectile that acts as a penetrator with enhanced lateral effect.

TYPE

AP

CALIBRE

30x165 mm

STANDARD

Eastern

PROCUREMENT AND COMPLIANCE

Supply is exclusively for government and institutional end-users. Availability is subject to destination screening, a state-issued export licence and a verified End-User Certificate.



02 / TECHNICAL SPECIFICATION

TECHNICAL DATA

30 mm x 165, PELE / AMMUNITION

IDENTITY AND CONSTRUCTION

Calibre	30 mm
Projectile mass	400±6 g

BALLISTIC PERFORMANCE

Muzzle velocity	970±15 m/s
Maximum pressure of powder gases	360 MPa
Operating temperature	-40 to +50 °C

DIMENSIONS, MASS AND SUPPLY

Round mass	853 g
------------	-------

ADDITIONAL TECHNICAL DATA

Status	Early development phase
--------	-------------------------