



01 / PRODUCT OVERVIEW

A-160

6.35 mm (.25 Auto) pistol cartridge



FIG 01 PRODUCT CONFIGURATION

3.25 g / 50 gr

BULLET MASS

**V12.5 = 230 ± 25
m/s**

AVERAGE VELOCITY

5.1 g

CARTRIDGE MASS

**6.35 mm (.25 Auto) Pistol
cartridge with
lead/antimony core bullet**

CALIBER AND TYPE

01.1 / OVERVIEW

A 6.35 mm (.25 Auto) pistol cartridge with a lead/antimony core ball bullet, made to C.I.P. and SAAMI standards for pistols of 6.35 mm calibre.

TYPE

Ball

CALIBRE

6.35 mm (.25 Auto)

PROCUREMENT AND COMPLIANCE

Supply is exclusively for government and institutional end-users. Availability is subject to destination screening, a state-issued export licence and a verified End-User Certificate.



TECHNICAL DATA

A-160 / AMMUNITION

IDENTITY AND CONSTRUCTION

Caliber and type	6.35 mm (.25 Auto) Pistol cartridge with lead/antimony core bullet
Bullet type	BALL
Bullet mass	3.25 g / 50 gr
Cartridge mass	5.1 g

BALLISTIC PERFORMANCE

Average velocity	V12.5 = 230 ± 25 m/s
Temperature interval	-30 °C to +52 °C

DIMENSIONS, MASS AND SUPPLY

Packing	5000 rds in cardboard box, 27.60 kg
---------	-------------------------------------

ADDITIONAL TECHNICAL DATA

Index	A-160
Usage	Pistol caliber 6.35 mm
Standard	C.I.P., SAAMI
Primer	small pistol, non corrosive, non mercuric, boxer
Propellant	single base flake powder