



01 / SYSTEM OVERVIEW

M06C

60 mm commando mortar M06C



FIG 01 COMMANDO CONFIGURATION VIEWS

60,75 mm

CALIBER

1600 m

MAXIMUM RANGE

20-25 rds/min

RATE OF FIRE

7,6 kg

MASS OF WEAPON IN COMBAT POSITION

01.1 / OVERVIEW

A 7,6 kg commando version of the 60 mm mortar with a 780 mm barrel and mechanical sight, firing HE M73 ammunition to 1600 m at 20-25 rds/min with a crew of two.

TYPE

Mortar

CALIBRE

60,75 mm

PROCUREMENT AND COMPLIANCE

Supply is exclusively for government and institutional end-users. Availability is subject to destination screening, a state-issued export licence and a verified End-User Certificate.



02 / TECHNICAL SPECIFICATION

TECHNICAL DATA

M06C / WEAPON SYSTEM

DIMENSIONS AND MASS

Caliber	60,75 mm
Length of barrel with breach piece	780 mm
Mass of weapon in travelling position	9 kg
Mass of weapon in combat position	7,6 kg
Dimension of box	1110 x 485 x 350 mm
Weight of box	22 kg

PERFORMANCE AND OPERATION

Elevation	-5° to +85°
Horizontal field of action without shifting of bipod	± 3°
Horizontal field of action with shifting of bipod	360°
Rate of fire	20-25 rds/min
Maximum range	1600 m
Minimum range	85 m
Maximum barrel pressure	250 bar

CONFIGURATION AND SUPPORT

Ammunition	HE M73
Sighting device	mechanical
Number of operators	2

ADDITIONAL TECHNICAL DATA

Packaging	4 pcs/box
Gross/Net	58 kg / 36 kg