



01 / PRODUCT OVERVIEW

M93

60 mm M93 HC smoke mortar bomb



FIG 01 PRODUCT CONFIGURATION

2400 m (0+4) (60 mm mortar M57, barrel length 720 mm)

MAXIMUM RANGE

300 m (0+1)

MINIMUM RANGE

1400 g

MASS WITH FUZE

414 bars

MAX. MEAN OPERATING PRESSURE

01.1 / OVERVIEW

60 mm screening smoke mortar bomb with 450 g HC composition, using the M98 ignition cartridge, ranging 300 m to 2400 m.

TYPE
SmokeCALIBRE
60 mmSTANDARD
NATO**PROCUREMENT AND COMPLIANCE**

Supply is exclusively for government and institutional end-users. Availability is subject to destination screening, a state-issued export licence and a verified End-User Certificate.



02 / TECHNICAL SPECIFICATION

TECHNICAL DATA

M93 / AMMUNITION

IDENTITY AND CONSTRUCTION

Length with fuze	330 mm
Mass with fuze	1400 g
Fuze	TP M67, pyrotechnical time fuze
Ignition cartridge	M98, waterproof

BALLISTIC PERFORMANCE

Maximum range	2400 m (0+4) (60 mm mortar M57, barrel length 720 mm)
Minimum range	300 m (0+1)
Max. mean operating pressure	414 bars
Operating temperature range	-30 deg C to +50 deg C

DIMENSIONS, MASS AND SUPPLY

Mass of HC composition	450 g
Packaging	1 shell per carton, 12 cartons per wooden box 52 x 40 x 20 cm, 30 kg, 0.042 m ³

ADDITIONAL TECHNICAL DATA

Increment charges	Ignition cartridge and four increment charges (0+4)
-------------------	---