



01 / PRODUCT OVERVIEW

A-579

7.62 x 54 mm Sniper rifle cartridge



FIG 01 PRODUCT CONFIGURATION

11,8 g / 182 gr

BULLET MASS

V25 = 780 ± 8 m/s

AVERAGE VELOCITY

24,9 g

CARTRIDGE MASS

**7.62 x 54 mm SNIPER
rifle cartridge with
lead/antimony core bullet**

CALIBER AND TYPE

01.1 / OVERVIEW

A 7.62 x 54 mm sniper rifle cartridge with a lead/antimony core SNIPER bullet and double base propellant, for 7.62 x 54 mm calibre weapons.

TYPE

Match

CALIBRE

7.62 x 54 mm

STANDARD

Eastern

PROCUREMENT AND COMPLIANCE

Supply is exclusively for government and institutional end-users. Availability is subject to destination screening, a state-issued export licence and a verified End-User Certificate.



02 / TECHNICAL SPECIFICATION

TECHNICAL DATA

A-579 / AMMUNITION

IDENTITY AND CONSTRUCTION

Caliber and type	7.62 x 54 mm SNIPER rifle cartridge with lead/antimony core bullet
Bullet type	SNIPER
Bullet mass	11,8 g / 182 gr
Cartridge mass	24,9 g

BALLISTIC PERFORMANCE

Average velocity	V25 = 780 ± 8 m/s
Temperature interval	-20 °C to +52 °C

DIMENSIONS, MASS AND SUPPLY

Packing	500 rds / cardboard case / 19,8 kg
---------	------------------------------------

ADDITIONAL TECHNICAL DATA

Index	A-579
Usage	7.62 x 54 mm caliber weapons
Primer	Large rifle, non corrosive, non mercuric, Berdan 6,55 DTN
Propellant	Double base powder