



01 / PRODUCT OVERVIEW

A-601

7.62 x 54 mm Match rifle cartridge



FIG 01 PRODUCT CONFIGURATION

12,3 g / 190 gr

BULLET MASS

**V25 = 765 ± 10
m/s**

AVERAGE VELOCITY

25,5 g

CARTRIDGE MASS

**7.62 x 54 mm MATCH
rifle cartridge with
lead/antimony core bullet**

CALIBER AND TYPE

01.1 / OVERVIEW

A 7.62 x 54 mm match rifle cartridge with a lead/antimony core bullet of type 303MK8Z, intended for 7.62 x 54 mm calibre weapons.

TYPE

Match

CALIBRE

7.62 x 54 mm

STANDARD

Eastern

PROCUREMENT AND COMPLIANCE

Supply is exclusively for government and institutional end-users. Availability is subject to destination screening, a state-issued export licence and a verified End-User Certificate.



02 / TECHNICAL SPECIFICATION

TECHNICAL DATA

A-601 / AMMUNITION

IDENTITY AND CONSTRUCTION

Caliber and type	7.62 x 54 mm MATCH rifle cartridge with lead/antimony core bullet
Bullet type	303MK8Z
Bullet mass	12,3 g / 190 gr
Cartridge mass	25,5 g

BALLISTIC PERFORMANCE

Average velocity	V25 = 765 ± 10 m/s
Temperature interval	-20 °C to +52 °C

DIMENSIONS, MASS AND SUPPLY

Packing	500 rds / cardboard case / 20 kg
---------	----------------------------------

ADDITIONAL TECHNICAL DATA

Index	A-601
Usage	7.62 x 54 mm caliber weapons
Primer	Large rifle, non corrosive, non mercuric, Boxer
Propellant	Double base powder