



01 / PRODUCT OVERVIEW

M72

82 mm reactive-cumulative round for recoilless gun M60



FIG 01 PRODUCT CONFIGURATION

390 m/s

MUZZLE VELOCITY

82 mm

CALIBRE

1000 m

RANGE

7.800 kg

WEIGHT

01.1 / OVERVIEW

82 mm rocket-assisted hollow-charge round for the M60 recoilless gun, for engaging tanks, armoured vehicles and fortified positions to 1000 m.

TYPE
HEATCALIBRE
82 mmSTANDARD
Eastern**PROCUREMENT AND COMPLIANCE**

Supply is exclusively for government and institutional end-users. Availability is subject to destination screening, a state-issued export licence and a verified End-User Certificate.



02 / TECHNICAL SPECIFICATION

TECHNICAL DATA

M72 / AMMUNITION

IDENTITY AND CONSTRUCTION

Calibre	82 mm
Fuze	Super quick UT M731

BALLISTIC PERFORMANCE

Muzzle velocity	390 m/s
Maximum pressure	750 bar
Angular penetration of armoured steel plate (Hb 340)	400 mm
Range	1000 m

DIMENSIONS, MASS AND SUPPLY

Weight	7.800 kg
Packaging	1 complete round per cardboard box; 3 boxes per wooden case, 110 x 34 x 13 cm, 0.047 m ³

ADDITIONAL TECHNICAL DATA

Explosive charge (TNT + RDX)	0.710 kg
Propellant charge NC	1.360 kg
Rocket charge NGR	0.900 kg
Muzzle safety	2.0 m
Ordinate	2 m
Primer	Electric