



01 / SYSTEM OVERVIEW

AK E2

AK E2 Assault Rifle



FIG 01 PRODUCT CONFIGURATION

7.62x39 mm

CALIBRE

620 +/- 60 rds/min

RATE OF FIRE

4.00 kgWEIGHT OF WEAPON WITH EMPTY
POLYMER MAGAZINE**30 rds**

MAGAZINE CAPACITY

01.1 / OVERVIEW

Gas-operated 7.62x39 mm assault rifle of the AK E group with a receiver-side rail for mounting a Picatinny rail adapter.

TYPE

Assault rifle

CALIBRE

7.62x39 mm

STANDARD

Eastern

PROCUREMENT AND COMPLIANCE

Supply is exclusively for government and institutional end-users. Availability is subject to destination screening, a state-issued export licence and a verified End-User Certificate.



02 / TECHNICAL SPECIFICATION

TECHNICAL DATA

AK E2 / WEAPON SYSTEM

DIMENSIONS AND MASS

Calibre	7.62x39 mm
Weight of weapon with empty polymer magazine	4.00 kg
Weight of polymer magazine	0.24 kg
Total length	934 mm / 689 mm with stock folded
Barrel length	415 mm

PERFORMANCE AND OPERATION

Rate of fire	620 +/- 60 rds/min
--------------	--------------------

CONFIGURATION AND SUPPORT

Magazine capacity	30 rds
Sights	Iron sights with tritium tubes, rear sight graduated to 1000 m

ADDITIONAL TECHNICAL DATA

Type of fire	Semi-automatic and automatic
Operation	Gas
Locking system	Rotating bolt
Rail interface	Picatinny rails at 12 and 6 o'clock on handguards; side rail on left of receiver
Options	Mount with Picatinny rail, underbarrel grenade launcher BGP 40 mm



CONFIGURATION VIEWS

AK E2 / SUPPLEMENTARY CATALOGUE VIEWS

FIG 02 / opposite side

