



01 / PRODUCT OVERVIEW

KT M71

Percussion gun primer KT M71



FIG 01 PRODUCT CONFIGURATION

2	percussion	2.065	max 23.9
POWDER MASS (G)	PRIMER TYPE	MINIMAL CONDITIONS FOR ACTION - IMPACT ENERGY (J)	PRIMER HEIGHT (MM)

01.1 / OVERVIEW

Airtight percussion gun primer for initiating the propellant charge of 57 mm, 76 mm, 85 mm, 100 mm, 122 mm, 130 mm and 152 mm gun and howitzer ammunition, safe in all conditions of transport, storage and use.

TYPE

Primer & booster

PROCUREMENT AND COMPLIANCE

Supply is exclusively for government and institutional end-users. Availability is subject to destination screening, a state-issued export licence and a verified End-User Certificate.



TECHNICAL DATA

KT M71 / AMMUNITION

BALLISTIC PERFORMANCE

Operating temperature (°C)	-30 ÷ +50
----------------------------	-----------

DIMENSIONS, MASS AND SUPPLY

Primer height (mm)	max 23.9
Primer diameter (mm)	max Ø30
Powder mass (g)	2
Primer mass (g)	85

ADDITIONAL TECHNICAL DATA

Primer type	percussion
Minimal conditions for action - impact energy (J)	2.065
Thread	SpW 27.178 x 14 pitches
Powder	black powder N°7
Applications	57 mm (antiaircraft gun S-60), 76 mm (mountain gun M48 B-1 and gun M42), 85 mm (antiaircraft gun M39/42 or M39/44), 100 mm (gun D-10 and antitank gun T-12), 122 mm (howitzer D-30 and M38), 130 mm (gun M46), 152 mm (gun-howitzer D-20 and M37)



CONFIGURATION VIEWS

KT M71 / SUPPLEMENTARY CATALOGUE VIEWS

FIG 02 / stamped face

