



01 / CAPABILITY OVERVIEW

Level III

Ballistic plate Level III (single or multi curve)



FIG 01 PRODUCT CONFIGURATION

≤ 1450 g

WEIGHT

Level III to NIJ STD
0101.04

PROTECTION LEVEL

plastic or fabric

EXTERNAL LAYER

single curve or
multi curve

CURVATURE

01.1 / OVERVIEW

A hard ballistic plate giving protection up to Level III of NIJ standard 0101.04, offered with a plastic or fabric external layer and produced as either single curve or multi curve for a comfortable fit front and back.

TYPE

Ballistic vest & plate

PROCUREMENT AND COMPLIANCE

Supply is exclusively for government and institutional end-users. Availability is subject to destination screening, a state-issued export licence and a verified End-User Certificate.



02 / TECHNICAL SPECIFICATION

TECHNICAL DATA

Level III / TECHNICAL EQUIPMENT

PERFORMANCE

Protection level	Level III to NIJ STD 0101.04
Additional protection	all types of common grain rifle ammunition, including 7.9 mm calibre

PHYSICAL DATA

Weight	≤ 1450 g
Plate dimensions	250 mm x 300 mm

ADDITIONAL TECHNICAL DATA

External layer	plastic or fabric
Curvature	single curve or multi curve
Ballistic data – 7.62 NATO Ball 150 grain M-80 FMJ	max. velocity 853 m/s
Ballistic data – 7.62 NATO Ball 150 grain M-80 (steel jacketed)	max. velocity 853 m/s
Ballistic data – 30-06 PSP 180 grain	max. velocity 824 m/s
Ballistic data – .30 Carbine 110 grain FMJ	max. velocity 595 m/s
Ballistic data – 12 Gauge rifled slug	max. velocity 473 m/s
Ballistic data – 7.62x39 mm Ball	max. velocity 732 m/s