



01 / CAPABILITY OVERVIEW

M20

M20 4x32 optical sight



FIG 01 PRODUCT CONFIGURATION

4x

MAGNIFICATION

7 deg

FIELD OF VIEW

<= 0.65 kg

MASS

+/-0-10

RECTIFICATION RANGE

01.1 / OVERVIEW

4x32 sight for automatic rifles at ranges up to 500 m, with reticle distance scales for 5.56 mm, 7.62 mm and 6.5 mm and a Picatinny adapter.

TYPE

Optical sight

PROCUREMENT AND COMPLIANCE

Supply is exclusively for government and institutional end-users. Availability is subject to destination screening, a state-issued export licence and a verified End-User Certificate.



02 / TECHNICAL SPECIFICATION

TECHNICAL DATA

M20 / TECHNICAL EQUIPMENT

PERFORMANCE

Magnification	4x
Field of view	7 deg
Rectification range	+/-0-10
Resolution	to 15 arcsec
Overtaking scale range	+/-0-04

INTERFACES AND OPERATION

Power supply	3 V CR2032 battery
Minimum work autonomy	200 h

PHYSICAL DATA

Exit pupil diameter	6 mm
Dimensions	140x80x75 mm
Mass	<= 0.65 kg

ADDITIONAL TECHNICAL DATA

Exit pupil distance	60 mm
Eyepiece diopter (fixed)	-0.5 dptr to -1.5 dptr
Reticle distance scale	100 m, 300 m, 500 m for 5.56 mm and 7.62 mm; 100 m, 300 m, 500 m, 800 m for 6.5 mm
Reticle illumination	LED



CONFIGURATION VIEWS

M20 / SUPPLEMENTARY CATALOGUE VIEWS

FIG 02 / opposite side, capped

