



01 / CAPABILITY OVERVIEW

RS-C

RS-C red dot reflex sight



FIG 01 PRODUCT CONFIGURATION

1x +/-0.1

MAGNIFICATION

**130 g including
power source**

MASS

+/-1 deg

RANGE OF SIGHT RECTIFICATION

**1 MOA (3 cm at
100 m)**

ADJUSTMENT STEP

01.1 / OVERVIEW

Compact red dot optoelectronic sight mounted on Picatinny rail through an adapter, for day, low visibility and night use combined with night vision devices.

TYPE

Reflex sight

STANDARD

NATO

PROCUREMENT AND COMPLIANCE

Supply is exclusively for government and institutional end-users. Availability is subject to destination screening, a state-issued export licence and a verified End-User Certificate.



02 / TECHNICAL SPECIFICATION

TECHNICAL DATA

RS-C / TECHNICAL EQUIPMENT

PERFORMANCE

Magnification	1x +/-0.1
Range of sight rectification	+/-1 deg

INTERFACES AND OPERATION

Power source	3 V CR2032 battery
Minimum work autonomy	> 100 h
Operating temperature	-30 deg C to +50 deg C

PHYSICAL DATA

Mass	130 g including power source
Dimensions	59x52x48 mm

ADDITIONAL TECHNICAL DATA

Adjustment step	1 MOA (3 cm at 100 m)
Reticle illumination	> 6 levels
Parallax	<= 0.2 dptr
Mounting	Picatinny rail via adapter